

Rolling Drum Riser



Understructure

Rolling Drum Riser complements your performance stage set-up. Its understructure has dual-locking casters to keep the riser in place during your performance. When not in use, its understructure collapses for easy storage and transport. The Rolling Drum Riser is for use with all Sightline Commercial Solutions' Platforms.



Dimensions and Weights

	8' x 8' x 13.5"H (1.22m x 2.44m x 0.34m)	8' x 8' x 16"H (1.22m x 2.44m x 0.41m)	8' x 8' x 18"H (1.22m x 2.44m x 0.46m)	8' x 8' x 24"H (1.22m x 2.44m x 0.61m)	8' x 8' x 30"H (1.22m x 2.44m x 0.76m)
Understructure (no platform)	43 lbs 19.5 kg	45 lbs 20.4 kg	48 lbs 21.8 kg	50 lbs 22.7 kg	55 lbs 24.9 kg

Other sizes available: 6' L x 6' W, 6' L x 8' W, custom

Technical Specifications

- Sets up in minutes with only two people
- When platforms are taken off, drum riser understructure folds up quickly and easily into storage position.
- Locking casters allow drum riser to roll into place and lock into static position
- Casters: 4" swivel locking casters on all main vertical columns.
- Main vertical members: 2" x 2" (51 mm x 51 mm) by 14 gauge carbon steel square tubing
- Main horizontal members: 2" x 2" (51 mm x 51 mm) by 14 gauge carbon steel square tubing
- Cross bracing: Low carbon HR flat bar
- Main pivot connection: steel tube bracket
- Finish Options: Black powder coat

